


STRATUS™ HIGH BAY RECTANGLE

FOOD PROCESSING
ETL SANITATION CERTIFIED TO NSF 2



FEATURES & SPECIFICATIONS

General Description

The Stratus™ LED high bay is an ideal light fixture choice for applications including warehouses, manufacturing facilities, cafeterias, and other areas with demanding environments. The Stratus™ is available in lumen packages equaling 400W through 1000W metal halide at mounting heights ranging from 15 to 65 feet. The Stratus™ high bay incorporates Illumitex's industry-leading and proprietary Aduro™ LEDs, resulting in near-perfect uniformity and exceptional delivered lumens and CBCP values in a sleek, aesthetically pleasing style.

Mechanical Construction

The body of the Stratus™ is constructed of precision CNC-machined, solid aluminum plate. LEDs and wiring are embedded into the fixture body and protected with two-part silicone potting to provide an IP66 rating on the LED side of the fixture. Formed and anodized aluminum wiring covers protect wiring connections to driver. Stainless steel hardware is used throughout. The Stratus™ mounting options include pendant, hook and yoke with power cord. Pendant mounting kit accessories including aircraft cable are also available (order separately).

Electrical Specifications

Class 1, 700mA LED driver is mounted directly to the back of the fixture. Input voltage options include 120-277VAC, 50/60Hz auto-sensing, consult factory for other voltages. Total harmonic distortion is below 20% and driver power factor is 0.90.

LEDs

Aduro™ LEDs incorporate Illumitex's patented, DD65 Digital Distribution™ technology, which delivers 65% of all lumens within the 50° beam angle. Color temperature options include 3000K, 4000K and 5700K CCT. LED packages offer an IP66 ingress protection rating against the intrusion of dust and moisture. Optic material is Acrymid® TT70 PMMI, that is highly heat and chemical resistant and offers excellent transmission and clarity.

Finish

Fixture finish is a high-performance Tiger Drylac® Super Durable powder coating suitable for both interior and exterior applications.

The Super Durable finish has excellent UV stability and weather resistance. Standard colors include white, gray, bronze and black. Custom colors are also available (contact factory for details).

Testing and Compliance

- 120,000-hour life to L90 @ 25°C ambient temperature
- 50,000-hour life to L70 @ 40°C ambient temperature
- -35°C to 55°C operating temperature range
- IP66 ingress protection rating option
- ETL/cETL Listed, IP66
- RoHS compliant
- DLC listed
- 5-year warranty



PART NUMBER ORDERING GUIDE

SHB	50			U				F
SERIES	BEAM ANGLE	# OF LEDs	COLOR TEMP (CCT)	VOLTAGE	FINISH ¹	DIMMING	MOUNTING & POWER FEED	OPTIONS
SHB = Stratus High Bay	50 = 50° Square	36 = 36 LEDs (square) 48 = 48 LEDs (square)	BW = 3000K (82 CRI) DW = 4000K (78 CRI) GW = 5700K (72 CRI)	U = 120-277VAC	BK = Black BZ = Bronze GR = Gray WH = White	N = Non-Dimmable D = Dimmable (0-10VDC) ²	C10 = 10-ft Power Cord ³ H10 = Hook with 10' Power Cord ³	F = ETL Listed to NSF 2

Notes:


1. Colors listed are standard finishes. Custom colors available; contact factory for details.
2. Dimming control wire is a 2-ft, 2-conductor cable for YKM option; a 10-ft, 2-conductor cable for C10 and H10 options;

3. C10 and H10 mounting options have a 10-ft, 3-conductor SO cord with no plug.


STRATUS™ HIGH BAY RECTANGLE

FOOD PROCESSING
ETL SANITATION CERTIFIED TO NSF 2

DIMENSION LINE DRAWINGS



SHB5036




SHB5048

MOUNTING LINE DRAWINGS


NOTE: All fixtures are factory sealed with power cords to meet ETL Sanitation listing to NSF 2

C10 Mounting



(Includes 10ft cord rigid, conduit mounting bracket)

H10 Mounting



(Includes 10ft power cord)

LUMINAIRE PERFORMANCE

Series	Input Watts (W)	Lumens (4000°K)	Lumens/Watt (4000°K)	Lumens (5700°K)	Lumens/Watt (5700°K)	Dimensions (in)	Weight (lbs)	Metal Halide Equivalent
SHB5036	316	27520	87.1	30965	98.0	19 x 38	36	750W
SHB5048	428	37147	86.8	41797	97.7	22.25 x 44.5	46	1000W

ACCESSORIES (Field installed - order separately)

Cat Logic	Description	Cat Logic	Description
ACT-5	5FT Aircraft Cable Hangers (2) with toggle end connectors	ACH-5	5FT Aircraft Cable Hangers (2) with captive hook end connectors
ACT-10	10ft Aircraft Cable Hangers (2) with toggle end connectors	ACH-10	5FT Aircraft Cable Hangers (2) with captive hook end connectors